



Certification Record

CUSTOMER	CLASS	FILE
American Power Conversion Corp. 85 Rangeway Rd Bldg 2, North Billerica MA 01862 USA	5842-05 CORD SETS - Multiple Receptacle Extension Boxes-	102418_0_000
	Refer to Class Description for program details	

- Cord connected multiple outlet extension box, with TVSS, Cat. Nos. DL7 and DL11VNT rated 15A, 125V ac, 60Hz.
- "Power Control Centre", with ac and telephone transient voltage surge protection, Model Nos POW5, POW6, POW5T, and POW6T; rated 120V ac, 60Hz, 15A.
- Surge Arrest Model Nos PER7, PER7T, PRO7, PRO7T, NET7, NET7T, NET8, NET9RM, PRO8, PER8, PER8T, PRO852C, PRO8T2MP12B and PRF8, rated 15A, 120V, 60Hz.
- Cord connected multiple outlet extension box with Transient Voltage Surge Suppression, Cat. Nos. P7GT, rated 15A, 120V ac, 60Hz.

TO THE REQUIREMENTS OF CSA STD 21, CSA STD 42 AND EN516:

- Cord connected multiple receptacle extension box (relocatable power taps), Type 3 SPD (Voltage Protection Rating: 400V ac L-N, 500V ac L-G and N-G), cat. nos. C2 and C2C, rated 15A, 125V ac, 60Hz.
- Cord connected multiple receptacle extension box (relocatable power taps), Type 3 SPD (Voltage Protection Rating: 600V ac L-N and N-G, 700V ac L-G), cat. nos. C3 and C3BLK, rated 15A, 125V ac, 60Hz.
- Cord connected multiple receptacle extension box (relocatable power taps), Type 3 SPD (Voltage Protection Rating: 600V ac L-N and N-G, 700V ac L-G), cat. nos. C5 and C5BLK, rated 15A, 125V ac, 60Hz
- Cord connected multiple receptacle extension box (relocatable power taps), Type 3 SPD (Voltage Protection Rating: 400V ac L-N, 600V ac L-G and N-G) cat. nos. G5 and G5BLK, rated 15A, 125V ac, 60Hz.
- Cord connected multiple receptacle extension box (relocatable power taps), Type 3 SPD (Voltage Protection Rating: 400V ac L-N, 500V ac L-G and N-G), cat. nos. P8T3, P8T3-CN, P8VT3, P11VT3, P11VT3-CN, P11VT3MP6, P11VT3MP10-CN, P11VNT3, P11VNT3-CN and P11GTV, rated 15A, 125V ac, 60Hz.
- Cord connected multiple receptacle extension box (relocatable power taps), Type 3 SPD (Voltage Protection Rating: 500V ac L-N and N-G, 600V ac L-G), cat. nos. P8V, P8VX577, P8VNTG, and P8VNTGX578, rated 15A, 125V ac, 60Hz.

TO THE REQUIREMENTS OF CSA STD 21, CSA STD 42 AND TIL A-24 AND EN516:

- Cord connected multiple outlet extension box with Transient Voltage Surge Suppression (SUPPRESSED VOLTAGE RATING: 330V PEAK, L-N, L-G, N-G), Cat. Nos. P7GT, rated 15A, 120V ac, 60Hz.
- Cord Connected Multiple Outlet Extension Boxes, rated at 15A, 120V ac, 60Hz:
Surge Arrest with transient voltage surge protection (SUPPRESSED VOLTAGE RATING: 330V

PEAK, L-N, L-G, N-G), Model Nos PER7, PER7T, PRO7, PRO7T, NET7, NET7T, NET8, NET9RM, PRO8, PRO8T2, PER8, PER8T.

- Multiple Extension Box, with Transient Voltage Surge Suppression (SUPPRESSED VOLTAGE RATING: 400V PEAK, L-N, N-G, 500V PEAK L-G), Cat Nos. CNS7Txx, P7Txx, P7VR, P7T6R, P7X, P74MP4 and P7V (where 'xx' represents the length of the power supply cord), rated 15A, 120V ac, 60Hz.
- Cord Connected Multiple Receptacle Extension Box, Series P6, with Transient Voltage Surge Suppression (SUPPRESSED VOLTAGE RATING: 400V PEAK, L-N, N-G, 500V PEAK L-G), Cat. Nos. P6H, P6B, P6BMP4 and CNS64, rated 15A, 120V ac, 60Hz.
- Cat. No. CNS63 rated 15A, 120V ac, has Surge Protection of 400V provided only Line-to-Neutral.
- Cord Connected Multiple Receptacle Extension Box, PDIY series, with Surge Protection (SUPPRESSED VOLTAGE RATING: 400V PEAK, L-N, N-G, 500V PEAK L-G), Cat. Nos. PDIY7, PDIY8, rated 15A, 120 V ac, 60Hz.

/ao.

Copyright © 2014 CSA International. All rights reserved.