


NG 160E/N/H circuit breakers NG 160NA switch-disconnectors


NG160E



NG160E (16 kA at 380/415 V)

	Rating	3P (10 x 9 mm modules)	4P (14 x 9 mm modules)
Fixed	16	28609	28619
	25	28608	28618
	32	28607	28617
	40	28606	28616
	50	28605	28615
	63	28604	28614
	80	28603	28613
	100	28602	28612
	125	28601	28611
	160	28600	28610


NG160N



NG160N (25 kA at 380/415 V)

	Rating	3P (10 x 9 mm modules)	4P (14 x 9 mm modules)
Fixed	16	28629	28639
	25	28628	28638
	32	28627	28637
	40	28626	28636
	50	28625	28635
	63	28624	28634
	80	28623	28633
	100	28622	28632
	125	28621	28631
	160	28620	28630

NG160H



NG160H (36 kA at 380/415 V)

	Rating	3P (10 x 9 mm modules)	4P (14 x 9 mm modules)
Fixed	16	28649	28659
	25	28648	28658
	32	28647	28657
	40	28646	28656
	50	28645	28655
	63	28644	28654
	80	28643	28653
	100	28642	28652
	125	28641	28651
	160	28640	28650



NG160NA switch-disconnectors

Rating	3P (10 x 9 mm modules)	4P (14 x 9 mm modules)
160	28265	28267

Add-on Vigi module



Bottom out

Rating	Sensitivity	Delay	3P (14 x 9 mm modules)	4P (14 x 9 mm modules)
160	Adjustable 30 mA at 3 A	Adjustable 0 - 60 - 150 ms	28310	28311



Top out



Rating	Sensitivity	Delay	3P (14 x 9 mm modules)	4P (14 x 9 mm modules)
160	Adjustable 30 mA at 3 A	Adjustable 0 - 60 - 150 ms	28312	28313



NG 160E/N/H and NG 160NA accessories

Connection accessories


Terminal shields (1 pair) for Vigi circuit breaker

	3P	28034
	4P	28035
		

Distribution connectors

	3 x 16 mm ²	Set of 4	19091
---	------------------------	----------	-------

Mounting accessories

	Din rail and 4 raisers for Acti 9 devices, length 342 mm		
		For 24 module enclosure	04227 ⁽¹⁾
	2 x	For 36 module enclosure	04227 ⁽¹⁾

Locking

Toggle locking device for 1 or 3 padlocks


	29370
---	-------

Electrical auxiliaries


Auxiliary contacts (changeover)

	OF or SD	29450
	OF or SD low level	29452

Voltage releases

	AC 50/60 Hz	Tension (V)	MX	MN
		48	28070	28080
		110/130	28071	28081
		220/240	28072	28082
		380/415	28073	28083
		440/480	28074	28084
	MN 220-240 V 50/60 Hz with time delay composed of:	MN 250 V DC		29421
		Delay unit 220-240 V 50/60 Hz		28088
				29427
DC	Voltage (V)	MX	MN	
	24	28075	28085	
	48	28076	28086	
	125	28077	28087	
	250	28078	28088	

Rotary handles

	Black extended handle	28061
	Red extended handle on yellow front	28060

⁽¹⁾ MGA parts.